MATERIAL SAFETY DATA SHEET $3M^{TM}$ Cavilon M No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, and 3345P 11/30/10



Material Safety Data Sheet

Copyright, 2010, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3MTM CavilonTM No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345,

3343E, 3344E, 3345E, 3343P, and 3345P

MANUFACTURER: 3M

DIVISION: Skin & Wound Care Division

ADDRESS: 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 11/30/10 **Supercedes Date:** 11/04/10

Document Group: 20-0585-8

Product Use:

Intended Use: Skin protectant barrier film.

SECTION 2: INGREDIENTS

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>% by Wt</u> |
|------------------------------------|-------------------|----------------|
| Foam applicator | Unknown | 92 - 96 |
| Hexamethyldisiloxane | 107-46-0 | 2 - 8 |
| Isooctane | 540-84-1 | 0.1 - 3 |
| Acrylate Terpolymer | Trade Secret | 0.1 - 1 |
| Polyphenylmethylsiloxane Copolymer | 73559-47-4 | < 0.5 |

Liquid is saturated onto foam applicator. There is no free-flowing liquid.

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Fluid on foam applicator or wipe.

Odor, Color, Grade: Foam applicator or wipe with clear, odorless liquid.

General Physical Form: Solid

Immediate health, physical, and environmental hazards: Flammable solid.

Page 1 of 7

MATERIAL SAFETY DATA SHEET 3MTM CavilonTM No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, and 3345P 11/30/10

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

No health effects are expected.

Inhalation:

No health effects are expected.

Ingestion:

No health effects are expected.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: No need for first aid is anticipated.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature 665 °F

Flash Point 14 °F [Test Method: Closed Cup]

Flammable Limits - LEL 0.8 % **Flammable Limits - UEL** 14.1 %

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

MATERIAL SAFETY DATA SHEET $3M^{TM}$ Cavilon M No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3344E, 3344E, 3345E, 3343P, and 3345P 11/30/10

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Flammable solid. The liquid absorbed onto the foam applicator has a flash point of 30 degrees F.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Ventilate the area with fresh air.

Environmental procedures

Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue. Seal the container.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Keep out of the reach of children. Avoid contact with oxidizing agents. Avoid eye contact with dust or airborne particles.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

8.2.2 Skin Protection

MATERIAL SAFETY DATA SHEET $3M^{TM}$ Cavilon TM No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, and 3345P 11/30/10

Not applicable. Avoid skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Do not ingest.

8.3 EXPOSURE GUIDELINES

None Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Fluid on foam applicator or wipe.

Odor, Color, Grade: Foam applicator or wipe with clear, odorless liquid.

General Physical Form: Solid **Autoignition temperature** 665 °F

Flash Point 14 °F [Test Method: Closed Cup]

Flammable Limits - LEL 0.8 % **Flammable Limits - UEL** 14.1 %

Boiling point 212 °F [*Test Method:* ASTM METHOD] [*Details:* (For liquid

portion)

Density 0.78 g/ml [*Details*: (For liquid portion)]

Vapor Density Not Applicable

Vapor Pressure <= 41 mmHg

Specific Gravity 0.78 [Test Method: ASTM METHOD] [Ref Std: WATER=1]

pH Approximately 7 [Details: (For liquid portion)]

Melting point

No Data Available

Solubility In Water <=.1 % [Test Method: ASTM METHOD]

Evaporation rate <=1 [Test Method: ASTM METHOD] [Ref Std: ETHER=1]

Volatile Organic Compounds 720 g/l [*Details:* (For liquid portion)]

Kow - Oct/Water partition coef Percent volatile88 - 94 %

VOC Less H2O & Exempt Solvents

No Data Available

Viscosity 5 centipoise [Test Method: ASTM METHOD] [Details: (For liquid

portion)]

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

MATERIAL SAFETY DATA SHEET $3M^{TM}$ Cavilon M No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, and 3345P 11/30/10

10.1 Conditions to avoid

Heat

Sparks and/or flames

10.2 Materials to avoid

Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide

Condition

During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

MATERIAL SAFETY DATA SHEET $3M^{TM}$ Cavilon M No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, and 3345P 11/30/10

44-0042-8868-2, 70-2007-4653-8, 70-2007-4654-6, 70-2007-4655-3, 70-2007-4656-1, 70-2007-4657-9, 70-2007-4658-7, 70-2007-4659-5, 70-2007-4660-3, 70-2007-6391-3, 70-2007-6392-1, 70-2007-6393-9, 70-2007-6490-3, 70-2007-6491-1, 70-2007-6492-9, 70-2007-6493-7, 70-2007-6555-3, 70-2007-6556-1, DH-8888-0045-4, DH-8888-1312-7, DH-8888-1313-5, DH-8888-1314-3, DH-8888-1344-0

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 3 Reactivity: 0 Special Hazards: None

MATERIAL SAFETY DATA SHEET $3M^{TM}$ Cavilon Mo Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, and 3345P 11/30/10

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 14: ID Number(s) Template 1 was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com